

BONIFACE

Champion 5T *Slidebed*

TM



Some optional equipment shown.

- *Shovel Tail Design for Low Approach*
- *Durable Lightweight Aluminium Deck*
- *Optional Second Car Lift*
- *Galvanised Subframe and Tilt Frame*
- *Optional Radio Remote Control*



Standard Features

- Aluminium Deck
- Aluminium Safety Side Rails
- Shovel Tail Design for Lower Approach Angle
- Bed Rollers Mounted in End of Deck
- 8 Lashing Rings on Deck (4 Per Side)
- Galvanised Subframe and Tilt Frame
- Manual Control Levers
- Hydraulic Winch with Wire Rope
- Hydraulically Sliding Winch Mechanism
- Manual Winch Free Spool
- Winch Roller Guide
- Towball Attachment
- Cab Control Unit
- Pump
- LED Marker Lights Fitted into Side of Bed (3 Per Side)
- 4 Ratchet Straps with Soft Eyes

Optional Features

- Additional Lashing Rings
- Wheel Chocks (pair)
- 2T Second Car Lift w/ Euro Wheel Grids
- 2T Second Car Lift w/ Century Wheel Lift
- Low Crash Bar
- Full Height Beacon Flyer
- 2, 4, 6, 8 or 12 Function Radio Remote Control
- PTO
- Plastic Locker
- Black Powder Coated Steel Locker
- Polished Stainless Steel Locker
- Granule Bin
- Plastic Mudguards Over Rear Wheels
- Aluminium Side Under-Run Protection
- 7 Pin Electrical Socket
- Side Winching Capstan-2 or 4 Position with Post
- Wheel Skate Bed Ramps
- Wheel Skates w/ Stowage (pair)
- GoJaks 6200 w/ Stowage (pair)
- Greedy Ramps w/ Stowage (pair)
- Ferrari Ramps w/ Stowage (pair)
- Wrecker Kit Stowed (Broom, Shovel, 7lb Sledge Hammer, 24" & 48" Bar, Hard Hat & 6 Safety Cones)
- 3T Trolley Jack Stowed in Locker
- Dynacycle Motorcycle Frame w/ Stowage
- Jump Leads
- Jump Socket
- LED Strobes Fitted into Front Grill (2x Amber)
- LED Strobes at Rear (2x Amber or Red)
- LED Beacon
- LED Work Lights
- LED Locker Lights
- LED Marker Lights on Flyer (6x)

Slidebed Specifications

Bed Length.....	7m
Bed Width.....	2.3m
Bed Rating.....	5 Tonne UDL
Bed Construction.....	Aluminium Extrusions
Winch Capacity.....	3.6 Tonne (EN 14492 Compliant)
Cable Diameter & Length.....	10mm x 24m
Cable Rating.....	7.2 Tonne MBL

Chassis Recommendations

GVWR*..... 12,000kg to 14,000kg

Note: All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Boniface Engineering Ltd. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown may be optional.

BONIFACE

Champion 5T Slidebed

TM



For more photos visit: boniface-eng.com/r/Champion-5T