





- Load Angle As Low As 4 Degrees
- No Need to Use Planks or Ramps
- Heavy Duty Rack and Pinion Drive
- Durable Lightweight Aluminium Deck
- Easy One-Button Operation of Bed

Standard Features

- Aluminium Deck
- · Heavy Duty Rack and Pinion Drive
- Power Assisted Fully Automatic Float Mechanism
- Bed Rollers Mounted in End of Deck
- 8 Lashing Rings on Deck (4 Per Side)
- Galvanised Subframe and Tilt Frame
- Front and Rear Body Locks
- Manual Control Levers
- Simple One Button Operation to Slide Bed Fully Off
- Hydraulic Winch with Wire Rope
- Manual Sliding Winch Mechanism
- Manual Winch Free Spool
- Winch Roller Guide
- Cab Control Unit
- LED Marker Lights Fitted into Side of Bed (3 Per Side)
- 4 Ratchet Straps with Soft Eyes
- Plastic Rear Mudguards w/ Mudflaps
- Pump
- Provision for 4 Position Side Winching Capstan

Optional Features

- Low Crash Bar
- Full Height Beacon Flyer
- 4 Function Radio Remote Control
- PTO
- Plastic Locker
- Black Powder Coated Steel Locker
- Polished Stainless Steel Locker
- 7 Pin Electrical Socket
- Towball Attachment
- Side Winching Capstan Post
- Wheel Skate Bed Ramps
- Wrecker Kit Stowed (Broom, Shovel, 7lb Sledge Hammer, 24" & 48" Bar, Hard Hat & 6 Safety Cones)
- Jump Leads
- Jump Socket
- LED Strobes Fitted into Front Grill (2x Amber)
- LED Strobes at Rear (2x Amber)
- LED Beacon
- LED Work Lights
- Side Under-Run Protection
- Additional Lashing Rings
- Wheel Chocks (pair)
- Wheel Skates w/ Stowage (pair)
- GoJaks 6200 w/ Stowage (pair)
- Greedy Ramps w/ Stowage (pair)
- Dynacycle Motorcycle Frame w/ Stowage

Slidebed Specifications

Bed Length	6.1m
Bed Width	2.2m
Bed Rating	3 Tonne UDL
Minimum Load Angle 4	to 6 degrees (Depending on Chassis)
Bed Construction	Aluminium Extrusions
Winch Capacity	3.6 Tonne (EN 14492 Compliant)
Cable Diameter & Length.	10mm x 24m

Chassis Recommendations

GVWR*......7,000 kg upwards

NOTE: All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Boniface Engineering Ltd. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown may be optional.







For more photos visit: boniface-eng.com/r/VLA-3T

