

BONIFACE

VLA 5T *Slidebed*

TM



Some optional equipment shown.

- *No Need to Use Planks or Ramps*
- *Double Rack and Pinion Drive*
- *Optional Second Car Lift*
- *Aluminium & Steel Deck Options*
- *Easy One-Button Operation of Bed*



Standard Features

- Aluminium Deck
- Double Heavy Duty Rack and Pinion Drives
- Power Assisted Fully Automatic Float Mechanism
- Bed Rollers Mounted in End of Deck
- 8 Lashing Rings on Deck (4 Per Side)
- Galvanised Subframe and Tilt Frame
- Front and Rear Body Locks
- Manual Control Levers
- Simple One Button Operation to Slide Bed Fully Off
- Hydraulic Winch with Wire Rope
- Manual Sliding Winch Mechanism
- Aluminium Side Under-Run Protection
- Manual Winch Free Spool
- Winch Roller Guide
- Pump
- Cab Control Unit
- LED Marker Lights Fitted into Side of Bed (3 Per Side)
- 4 Ratchet Straps with Soft Eyes
- Provision for 4 Position Side Winching Capstan

Optional Features

- Steel Deck (7m x 2.3m)
- Additional Lashing Rings
- Wheel Chocks (pair)
- 2T Second Car Lift w/ Euro Wheel Grids
- 2T Second Car Lift w/ Century Wheel Lift
- Low Crash Bar
- Full Height Beacon Flyer
- 4 Function Radio Remote Control
- PTO
- Plastic Locker
- Black Powder Coated Steel Locker
- Polished Stainless Steel Locker
- Granule Bin
- Plastic Mudguards Over Rear Wheels
- 7 Pin Electrical Socket
- Towball Attachment
- Side Winching Capstan Post
- Wheel Skate Bed Ramps
- Wheel Skates w/ Stowage (pair)
- GoJaks 6200 w/ Stowage (pair)
- Greedy Ramps w/ Stowage (pair)
- Ferrari Ramps w/ Stowage (pair)
- Wrecker Kit Stowed (Broom, Shovel, 7lb Sledge Hammer, 24" & 48" Bar, Hard Hat & 6 Safety Cones)
- 3T Trolley Jack Stowed in Locker
- Dynacycle Motorcycle Frame w/ Stowage
- Jump Leads
- Jump Socket
- LED Strobes Fitted into Front Grill (2x Amber)
- LED Strobes at Rear (2x Amber or Red)
- LED Beacon
- LED Work Lights
- LED Locker Lights
- LED Marker Lights on Flyer (6x)

Slidebed Specifications

Bed Length.....	7m
Bed Width.....	2.3m
Bed Rating	5 Tonne UDL
Minimum Load Angle ..	3 to 5 degrees (Depending on Chassis)
Bed Construction	Aluminium Extrusions
Winch Capacity	3.6 Tonne (EN 14492 Compliant)
Cable Diameter & Length	10mm x 24m
Cable Rating.....	7.2 Tonne MBL

Chassis Recommendations

GVWR*..... 12,000kg to 14,000kg

Note: All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Boniface Engineering Ltd. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown may be optional.

BONIFACE

VLA 5T

Slidebed

TM



For more photos visit: boniface-eng.com/r/VLA-5T