

# **BONIFACE**

## **Interstater Mk6**

TM



*Some optional equipment shown.*

- *Industry Favourite for Heavy-Duty Towing*
- *2 Low Profile Under-lift Options*
- *Optional Winch Capacity*
- *Rear Outboard Legs with Pivoting Feet*
- *Optional Sidewinder Pivoting Front Legs*

[boniface-eng.com](http://boniface-eng.com)



## Standard Features

- Maxireach Lowline H or Lowline I Under-Lift
- Tailboard D Rings
- D Loops on Rear Feet
- Super Deluxe Stainless Steel Tri-Step Body
- Large Wardrobe Style Doors on Front Lockers
- Single Door Access for "Most Used Equipment"
- Coach Style Double Catch Door Locks
- Internal Hinges
- Gas Strut Door Shuts
- Weather Proof Seals Around All Doors
- Vertically Opening Doors Over Rear Wheels
- Flat Floor Lockers with No Door Sills
- Stealth Flyer with Environment Lights
- Control Station at Rear
- Ballast
- LED Work lights (4x)
- LED Locker Lights
- Dri-Dek Locker Matting

## Optional Features

- Boniface Lift Bar with Low, High and Extra High Pedestals, Chain Clutches, Spring Hanger Adaptors, King Pin Adaptor and 3 Sets of Standard Forks
- Super Heavy Duty Wheel Grids w/ Stowage
- Euro Wheel Grids w/ Stowage
- Century Wheel Grids w/ Stowage
- Heavy Duty Tow Pole w/ Stowage
- Customised Stowage Plan
- Additional Lifting Forks and Pedestals
- Planetary Winch w/ Air Free Spool (Max. 2)
- Rear Inboard Legs
- Rear Outboard Legs
- 8, 10 or 12 Function Radio Remote
- Sidewinder
- Sidewinder Winch (Max. 2)
- Sidewinder Fairlead
- Sidewinder Leg Covers
- 3 Drawer Tool Box
- 4 Drawer Tool Box
- Air Reel
- Electric Reel
- Trailer Board
- Rear View Camera System (Single or Double)
- Central Locking for Locker Doors
- Half Shaft Stowage in Locker or Tailboard
- Hand Wash Basin with Soap & Towel Dispenser
- Jump Leads
- Jump Sockets (12 and 24 Volt)
- Stainless Steel Hand Rails
- Stainless Steel Kick Plates
- Snatch Blocks
- Safety Chains
- Aluminium Wheel Stands
- Granule Bin
- Fire Extinguisher
- Additional LED Beacon
- Additional Work Lights
- Additional LED Side Markers

## Optional Features (continued)

- Under-Lift Boom Work Lights
- LED Strobe Lights (Red or Amber)
- Docking Lights
- Range of Flyers
- Wrecker Kit

## Specifications

|                                          |          |
|------------------------------------------|----------|
| Under-Lift Capacity Retracted: . . . . . | 33 Tonne |
| Under-Lift Capacity Extended: . . . . .  | 9 Tonne  |
| H Boom Extended: . . . . .               | 4.34m    |
| H Boom Retracted: . . . . .              | 2.04m    |
| I Boom Extended: . . . . .               | 3.79m    |
| I Boom Retracted: . . . . .              | 1.86m    |
| Subterranean travel: . . . . .           | 110mm    |
| Negative tilt: . . . . .                 | -10°     |
| Positive tilt: . . . . .                 | +18°     |

## Chassis Recommendations

The Interstater will fit a wide range of chassis configurations including 2, 3, and 4 axle vehicles. Please contact our sales team for more information.

Note: All ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Boniface Engineering Ltd. reserves the right to change or modify product and/or specifications without notice or obligation. Some equipment shown maybe optional.



For more photos visit: [boniface-eng.com/r/Interstater](http://boniface-eng.com/r/Interstater)